MENDUCI

# SURFACE MOUNT H.V.M CRASH GATE 40

IWA 14 Crash Tested to Stop a 7.2 Tonne Truck Travelling at 40mph/64kmh at 90°









### NO PINNING TO THE SURFACE H.V.M INSTALL IN 2 HOURS



The Safetyflex design team have responded to clients' requirement for a new type of surface mount gate that can be installed within 2-3 hours, with no man handling to operate the gate, and the gate to open horizontally to save ground space.a



11 Cooper St, Smithfield, 2164, NSW 1300 558 304 www.ezisecurity.com.au





## **SURFACE MOUNT H.V.M**

### **CRASH GATE 40**

Designed to stop a car and truck with one front gate



safetyflex





FOOTING DEPTH

SURFACE MOUNTED

SURFACE MOUNTED



### NO MAIN POWER NEEDED

VEHICLE

SPEED

80

48

VEHICLE

CLASS

N3C

N2A

SPRINGLINE 30 & 50-SM IWA14-1 VEHICLE PERFORMANCE CLASSIFICATION

VEHICLE

ANGLE

90

VEHICLE

PENETRATION

6.8

5.4

## safety fle

- Police Stations
- Airports
- Critical Infrastructure
- Government Buildings
- Conference Cnetres

VEHICLE TEST

V/7200 KG

V/7200 KG

This br design off roa

The ne Horiba 7.5 to vehicle

There i the ga less dri on the

**OPERATES** WITH AN **18 VOIT CORDLESS DRILL** 

